



COLLISION PROTECTION

Working in tight spaces at speed can lead to mis-hap. The rear impact protection helps protect the engine and drive from collisions.




KEYLESS START

All you need to do is enter a PIN code for ignition. Handing over keys when changing drivers is a problem of the past.



SIMPLE CUTTING HEIGHT ADJUSTMENT

The cutting height of the mower can be easily and finely adjusted from the seat via a rotary wheel.



POWERFUL MOWERS

The mowers produce an excellent finish. The drive is easily accessible for maintenance via a flap in the driver platform.

Model		ZXR48-EU	ZXC48SE-EU	ZXR54-EU	ZXC54SE-EU
Engine					
Field of application		Private use	Commercial use	Private use	Commercial use
Manufacturer / Type		Briggs & Stratton Professional Series™	Briggs & Stratton Commercial Series™	Briggs & Stratton Professional Series™	Briggs & Stratton Commercial Series™
Maximum engine power	hp (kW)	24 (17.89)	25 (18.64)	24 (17.89)	25 (18.64)
Engine capacity	cc	724	724	724	724
Choke		Automatic	Manual	Automatic	Manual
Type of fuel		Petrol	Petrol	Petrol	Petrol
Fuel tank capacity	l	28.4 (1 tank, left-hand side)	47.3 (2 tanks, left & right)	28.4 (1 tank, left-hand side)	47.3 (2 tanks, left & right)
Mower deck					
Cutting width	cm	122	122	137	137
Cutting height	mm	38 - 127	38 - 127	38 - 127	38 - 127
Type		Welded	Welded	Welded	Welded
Discharge		Lateral (discharge channel from moulded rubber)	Lateral (discharge channel from moulded rubber)	Lateral (discharge channel from moulded rubber)	Lateral (discharge channel from moulded rubber)
Mower deck lift / lower		Mechanical via ergonomic foot pedal	Mechanical via ergonomic foot pedal	Mechanical via ergonomic foot pedal	Mechanical via ergonomic foot pedal
Number of guide wheels (F/R)		6 (4/2)	6 (4/2)	6 (4/2)	6 (4/2)
Mulch kit		Optional	Optional	Optional	Optional
Drive train					
Manufacturer / Type		Hydrogear ZT2800	Hydrogear ZT3400	Hydrogear ZT2800	Hydrogear ZT3400
Drive shaft (diameter)	mm	25.4	28.6	25.4	28.6
Torque	Nm	406	677	406	677
Maximum speed (forward)	km/h	12.9	16.1	12.9	16.1
Hand brake		Integrated in axle	Integrated in axle	Integrated in axle	Integrated in axle
PTO					
Switch		Electronic	Electronic	Electronic	Electronic
Coupling		Standard	Heavy Duty	Standard	Heavy Duty
Electrics					
Voltage	Volt	12	12	12	12
Dimensions					
Length	mm	2,050	2,050	2,050	2,050
Width (tyre to tyre)	mm	1,278	1,303	1,278	1,303
Width (Inc. discharge channel)	mm	1,711	1,711	1,711	1,711
Height (inc. folding bracket)	mm	1,791	1,816	1,791	1,816
Wheelbase	mm	1,232	1,232	1,232	1,232
Curb weight	kg	413	434	413	434
Tyres					
Front		13x5-6	13x6.5-6	13x5-6	13x6.5-6
Rear		22x9.5-10	23x10.5-12	22x9.5-10	23x10.5-12
Seat					
Suspension		-	Premium suspension with a high backrest	-	Premium suspension with a high backrest
Horizontal adjustment		Std.	Std.	Std.	Std.
Backrest		Normal	Extra high	Normal	Extra high
Armrest		Std.	Std.	Std.	Std.
Security					
Folding bracket		Std.	Std.	Std.	Std.
Contact seat switch		Std.	Std.	Std.	Std.
Coded ignition		Std.	Std.	Std.	Std.
Extras					
LED work lights		Opt.	Std.	Opt.	Std.
Additional work spotlight		Opt.	Opt.	Opt.	Opt.
Additional mower guide wheels		Opt.	Opt.	Opt.	Opt.
Rear towing eye		Opt.	Std.	Opt.	Std.
Area performance					
80% productivity	ha/h (ca.)	1.41	1.76	1.41	1.76