



ADJUSTABLE STEERING WHEEL

The CS2520 HGE adjustable steering column allows drivers of all sizes to work comfortably.



INDEPENDENT PTO SWITCH

The independent PTO clutch on the CS2520 HGE premium model offers easy PTO engagement.



FRONT LOADER CONTROL LEVER

The CS2520 is equipped with a four-way control lever for the comfortable operation of a front loader or other ancillary equipment.



CRUISE CONTROL

Optional with the CS 2520 HGE, the electrically switch-able cruise control allows the driving speed to be fixed at the touch of a button.



RETROFIT CABIN (KIOTI)

The CS2520 HGE can be retrofitted with a KIOTI 4-post cab, offering great all-round visibility and protection from the weather.



FRONT LINKAGE & PTO (Matev)

The CS 2510 H & CS2520 HGE can be fitted with a front linkage and PTO, enabling the operation of front mounted equipment, boosting the tractor's capabilities.



FRONT MUD GUARDS

The CS2510 H and CS2520 HGE models can be fitted with optional front mud guards to protect the platform or cab from mud and water splashes.



MID-MOUNTED MOWER

Available for all CS models, the SM mid-mounted mower decks, turn the CS into a dedicated mowing machine. More information about the mowers can be found on page 50.

Model		CS2220U-EU	CS2510H-EU	CS2520H-GE	CS2520GE/CH
		Roll bar	Roll bar	Roll bar	Cabin
Motor					
Manufacturer		KIOTI	KIOTI	KIOTI	KIOTI
Control		Mechanical	Mechanical	Mechanical	Mechanical
Emissions tier		5	5	5	5
Maximum power (ECE-R120)	hp (kW)	21.3 (15.7)	24.8 (18.3)	24.8 (18.3)	24.8 (18.3)
Number of cylinders		3	3	3	3
Engine displacement	cc	1,007	1,007	1,007	1,007
Rated speed	rpm	3,200	3,200	3,200	3,200
Turbocharger		No	No	No	No
Fuel tank	l	23.5	25.5	25.5	25.5
Power-train					
Transmission		Mechanical gearbox	HST - Hydrostatic	HST - Hydrostatic	HST - Hydrostatic
Number of gears or HST ranges		1,047	2 ranges	2 ranges	2 ranges
Shuttle Type		1&R synchronized	-	-	-
Maximum speed (forward)	km/h	1.1-19.3	0-16.5	0-16.5	0-16.5
Four-wheel drive		Std.	Std.	Std.	Std.
Differential lock		Std. (rear axle)	Std. (rear axle)	Std. (rear axle)	Std. (rear axle)
Steering type		Hydr. Power steering	Hydr. Power steering	Hydr. Power steering	Hydr. Power steering
PTO					
Rear PTO	rpm	540	540	540	540
Rated PTO power	hp	17.6	18.7	18.7	18.7
Rear PTO clutch		Foot clutch	Mech. engagement	Elec- hydr. engagement	Elec- hydr. engagement
Mid PTO	rpm	Std. 2,200	Std. 2,200	Std. 2,200	Std. 2,200
Front PTO (from intermediate axles)	rpm	- -	Opt. 2,200	Opt. 2,200	Opt. 2,200
Front PTO (by engine)	rpm	- -	- -	- -	- -
Hydraulics					
Number of double-acting spools at the rear		1 (Opt.)	1 (std.)	1 (std.)	1 (std.)
Four-way cross control lever		With front loader	With loader or front linkage.	Std.	Std.
Number of double-acting spools		3	3	3	3
Pump power (work / steering)	l/min	25.7 (18.6 / 7)	25.7 (18.6 / 7)	26.4 (18.7 / 7.7)	26.4 (18.7 / 7.7)
Pressure	bar	140	140	140	140
Three-point linkage (rear)					
Regulation		Hydr. adjustable	Hydr. adjustable	Hydr. adjustable	Hydr. adjustable
Category		Cat 1	Cat 1	Cat 1	Cat 1
Maximum lifting capacity	kg	877	877	871	871
Lifting capacity at the coupling point (entire stroke)	kg	715	715	715	715
Lifting capacity 610mm behind coupling point (entire stroke)	kg	318	318	318	318
Three-point linkage (front)					
Available		-	Opt.	Opt.	Opt.
Category		-	Cat 0	Cat 0	Cat 0
Dimensions					
Total length (incl. three-point linkage)	mm	2,623	2,523	2,523	2,523
Width	mm	1,185 (turf tyres)	1,185 (turf tyres)	1,185 (turf tyres)	1,185 (turf tyres)
Total height (roll bar)	mm	2,285 (turf tyres)	2,285 (turf tyres)	2,285 (turf tyres)	-
Total height (cabin)	mm	-	-	-	1,981 (turf tyres)
Wheelbase	mm	1,500	1,400	1,400	1,400
Min. ground clearance	mm	234 (turf tyres)	234 (turf tyres)	234 (turf tyres)	234 (turf tyres)
Weight (roll bar)	kg	710	700	705	-
Weight (cabin)	kg	-	-	-	918
Permissible total weight	kg	1,360	1,225	1,295 -1,540	1,295 -1,540
Ab. Front axle load (max.)	kg	650	650	650	650
Ab. Rear axle load (max.)	kg	1,000	1,000	1,000	1,000
Towing capacity					
B1 - un-braked	kg	330	330	330	330
B2 - Overrun braked	kg	2,000	2,000	2,000	2,000
Extras					
Air conditioning		-	-	-	-
Swivel steering column		-	-	Std.	Std.
Cruise Control		-	Opt.	Opt.	Opt.
HST Link (HST / engine speed coupling)		-	Opt.	Opt.	Opt.
Stationary PTO operation		Std.	-	Std.	Std.