



# K9 2410 UTILITY VEHICLE

ROPS | Field Cabin | Factory Cabin



**2**  
**YEARS'**  
**WARRANTY**  
**(Unlimited**  
**Hours)**

**KIOTI**

*more than tractors*





## THE UTV FOR ALL TERRAINS & JOBS

No matter what the job or specification, the K9 2410 utility vehicle from KIOTI gets the job done. Whether travelling off-road or on the highway, a choice of ROPS, canopy and screen, or full cabin keeps the driver and passengers safe.

The generously sized rear load area can carry loads up to 500kg from maintenance equipment to soil, stone and livestock feed. Protected with a Urethane coating, the bed should stay looking good for many years, whilst the easy opening rear door and assisted tipping allows rapid unloading of bulk materials.

A 25hp KIOTI engine provides the power, with a variable CVT transmission, with high / low and reverse ranges, provides the drive through a choice of two or four wheel drive.

Capable of safely carrying three people, the spacious cabin is comfortable, well laid out and provides convenient storage.



### KIOTI DIESEL POWER

The 25 hp stage V compliant 3-cylinder diesel engine provides plenty of power and torque. The sub 25hp rating means exhaust gas treatment is not required.



### GREAT GROUND CLEARANCE

All-round wishbone suspension gives the 2410C-EU a ground clearance of 265mm and the 2410U-EU 317mm ground clearance.



### COMFORTABLE & SAFE

Fitted with 3 seats, each with a safety belt, the cabin provides safe transport for the driver plus two passengers.



### 500KG LOAD AREA

The large urethane coated loading area - with a payload capacity of 500 kg - makes working with the K9 particularly easy. assisted tipping operation is available as an option.



## Agriculture & Equine

Whether feeding livestock, working in the lambing field, erecting fences or maintaining paddocks, the K9 is at home on the farm or around the livery yard.

A variety of materials can be carried either in the large load area or in a trailer pulled by the rear draw-bar.

The selectable 4WD and generous ground clearance ensures the K9 tackles off road terrain effortlessly.

The fully enclosed heated cabin provides comfort during the winter months.



## K9 Series



## Sports Turf Maintenance

Predominantly found on golf and race courses, the K9 is used for a range of sports turf maintenance applications.

Whether re-seeding or repairing sports turf, the K9 can usefully carry, sand, soil, seed or fertiliser to the required areas.

The optional low tread tyres provide good traction with minimal surface disturbance.

Maintenance teams can keep cool on hot summer days by the 2410C-EU's fully air-conditioned factory fit cabin, or the fully opening windscreen standard on all models.

## Estate Management

Private and commercial estate owners and maintenance crews can benefit from using a K9 UTV.

The three-seater cabin provides comfortable transportation for three adults, useful when a larger crew is required.

The rear load area can carry an assortment of tools and equipment or can be used to remove waste and vegetation.

The K9 is available in KIOTI red, or green for a more subtle option.







The Utility Vehicle for all Terrains and Jobs

## K9 2410U-EU

All-round wishbone suspension, speed-proportional electric, power steering (EPS), a 50 km/h homologated CVT transmission, engine brake hill descent control. Hydraulic disc brakes and a generous 317mm ground clearance allows the K9 to tackle off road terrain and highways in equal measure. Operators using their K9 in rough terrain can protect the underneath by fitting a skid plate.

The illuminated dashboard and additional work lights provide a clear view when working in the dark. The steering wheel and seat can be adjusted to suit the driver's requirements.

Available in KIOTI red or green and with a choice of wheels & tyres, the K9 can be easily customised.



**HYDRAULIC DISC BRAKE**

Durable, hydraulic disc brakes front and rear ensure excellent safety even when travelling at top speed fully laden.



**INDEPENDENT SUSPENSION**

Both the front and rear wheels are suspended individually via robust double wishbones, ensuring a pleasant ride in any terrain.



**CVT TRANSMISSION**

Drive is provided by a belt driven CVT transmission with H/L/N/R ranges. Selectable 4WD and a limited slip differential on the front axle provide extra traction when needed.



**ENGINE BRAKE**

The engine brake works with the CVT transmission to provide additional braking, especially useful when descending hills loaded or towing.





## LIVESTOCK CANOPY

Ideal for transporting young livestock safely and galvanised for protection and durability. The livestock canopy can be specified with 2 x swinging or 1 x up and over doors.

## CABIN OPTIONS

With versatility in mind, the K9 2410U-EU can be fitted with a number of cabin configurations to suit a wide range of operations.

As standard, the K9 2410-EU is fitted with a full ROPS protection frame, with the following options available:

- Plastic sun canopy
- Opening front windscreen and wiper
- Rear mesh guard
- Plastic rear window
- Half door kit
- Soft cabin kit

Alternatively, the K9 2410U-EU can be fitted with a fully enclosed retro-fit field cabin, complete with fully opening windscreen and wiper, full glass doors and optional sliding side window, for great ground visibility, plus a cabin heater for winter comfort.



## WINDSCREEN & WIPER

When fitted, the fully opening windscreen and windscreen wipers protect the driver and passengers from wind and bad weather and ventilated in warmer weather.



## DASHBOARD

The ergonomic dashboard is well illuminated with key controls easily located. The instrument panel contains a speedometer, hour meter, fuel gauge, coolant temp gauge and turning indicators.





Adding comfort and sophistication to the range

## K9 2410C-EU

Offering increased comfort and sophistication, the 2410C-EU is fitted with a fully air-conditioned factory fitted cabin as standard, providing a comfortable work environment all year round.

The generous 265mm ground clearance combines well with the selectable 4-wheel drive and wishbone suspension to provide a comfortable ride off-road and on the highway.

In addition to the features found on the K9 2410U-EU, the 2410C-EU is equipped with rear headrests and floor mat. There are many options. The manual load deck tipping can be upgraded to electric for easier operation.



**ELECTRIC POWER STEERING**

The speed proportional electric power steering (EPS) gives more responsive steering. The faster the speed the more resistance the driver feels through the steering wheel.



**FACTORY FITTED CABIN**

The factory fitted cabin provides a comfortable work environment. Fitted with half glazed doors, the cabin is Insulated for greater temperature and noise control, A radio can be fitted as an option.



**ENGINE BRAKE**

The engine brake works with the CVT transmission to provide additional braking, especially useful when descending hills loaded or towing.



**AIR CONDITIONED CABIN**

The fully air-conditioned cab keeps the crew comfortable all year round, cool in summer and warm in winter.

## Standard Equipment

On all K9 UTVs



### STORAGE

Large and convenient storage areas are built into the dashboard for the secure storage of essential items.



### 12V AND USB PORTS

Thanks to the 12V and USB ports, various devices can be conveniently charged or powered whilst driving.



### HITCH

The K9 comes with a clevis hitch at the front and a clevis draw bar at the rear complete with pins.



### LIGHTING

The K9 is equipped with road lights for great visibility.


## Optional Equipment

Available on 2400-EU or 2400C-EU



### ATV TYRES

25 x 10 - 12 cleated ATV tyres provide excellent traction in muddy and rough terrain.



### GENERAL PURPOSE TYRES

25 x 10 - 12 Worksite off-road tyres provide an all-round solution, great off-road or on the highway.



### GRASS TYRES

25 x 10 - 12 grass tyres protect the grass sward whilst providing traction in slippery conditions.



### LARGE ATV TYRES

26 x 10 - 12 Pro terrain cleated ATV tyres provide excellent traction in muddy and rough terrain with a larger foot print.




### STEEL WHEELS

A practical, robust and affordable wheel, all tyre options can be fitted. (2400U-EU only).



### ALLOY WHEELS

Strong and robust with added aesthetics, all tyre options can be fitted.



### SKID PLATE

The optional skid plate protects the chassis and exposed components from damage by rough and undulating terrain.



### WORK LIGHTS

Work light kits are available as an option, increasing safety and visibility in low light.



| Model  |         | K9 2410U-EU<br>(red or green)                                 | K9 2410C-EU<br>(red or green)                                 |
|--|---------|---|---|
| <b>Engine</b>                                    |         |   |   |
| Type   |         | Water-cooled three-cylinder<br>4-stroke diesel in-line engine | Water-cooled three-cylinder<br>4-stroke diesel in-line engine |
| Manufacturer                                     |         | KIOTI   | KIOTI   |
| Emission tier                                    |         | Stage 5 compliant   | Stage 5 compliant   |
| Maximum engine power                             | hp (kW) | 24.3 (18)   | 24.8 (18,3)   |
| No. of cylinders                                 |         | 3   | 3   |
| Engine displacement                              | cc      | 1,007   | 1,007   |
| Rated speed                                      | rpm     | 3,200   | 3,200   |
| Fuel tank capacity                               | l       | 37  | 37  |
| <b>Drive train</b>                               |         |   |   |
| Type   |         | Drive belt, continuously variable (CVT)                       | Drive belt, continuously variable (CVT)                       |
| Gear ranges                                      |         | L-H-N-R   | L-H-N-R   |
| Maximum speed (forward)                          | km/h    | 0 - 50  | 0 - 50  |
| Brakes   |         | Hydraulically disc brakes all round                           | Hydraulically disc brakes all round                           |
| Engine brake                                     |         | Std.  | Std.  |
| <b>Wheel suspension</b>                          |         |   |   |
| <b>Front wheel suspension</b>                    |         | Independent, double wishbone                                  | Independent, double wishbone                                  |
| Front suspension: total                          | mm      | 170   | 130   |
| Front suspension: compression                    | mm      | 35  | 35  |
| Front suspension: extension                      | mm      | 135   | 95  |
| <b>Rear wheel suspension</b>                     |         | Independent, double wishbone                                  | Independent, double wishbone                                  |
| Rear suspension: total                           | mm      | 200   | 160   |
| Rear suspension: compression                     | mm      | 110   | 70  |
| Rear suspension: extension                       | mm      | 90  | 90  |
| <b>Steering</b>                                  |         |   |   |
|  |         | Electric power steering (EPS)                                 | Electric power steering (EPS)                                 |
| <b>Dimensions</b>                                |         |   |   |
| Overall length                                   | mm      | 3,045   | 3,045   |
| Overall width                                    | mm      | 1,590   | 1,640   |
| Overall height with sun canopy                   | mm      | 1,950   | -   |
| Overall height with full cabin                   | mm      | 2,050   | 1,990   |
| Wheel base                                       | mm      | 2,180   | 2,180   |
| Min. ground clearance                            | mm      | 317   | 265   |
| Unladen weight (basic equipment)                 | kg      | 930   | 1,050   |
| Loading area payload                             | kg      | 500   | 500   |
| Total payload                                    | kg      | 770   | 650   |
| Permissible total weight                         | kg      | 1,700   | 1,700   |
| Tow-able load (unbraked)                         | kg      | 590   | 530   |
| Turning radius                                   | m       | 4.6 (2WD)   | 4.6 (2WD)   |
| <b>Loading area</b>                              |         |   |   |
| Length x width x height                          | mm      | 1,110 x 1,480x293   | 1,110 x 1,480x293   |
| Single-hand tailgate op                          |         | Std.  | Std.  |
| Assisted bed tipping device                      |         | Elec.   | Elec.   |
| <b>Wheels &amp; Tyres</b>                        |         |   |   |
| Wheel rims                                       |         | Steel or alloy  | Alloy   |
| ATV off-road tyres                               |         | Front 25x10x12, rear 25x10x12                                 | Front 25x10x12, rear 25x10x12                                 |
| General purpose Worksite tyres                   |         | Front 25x10x12, rear 25x10x12                                 | Front 25x10x12, rear 25x10x12                                 |
| Grass tyres                                      |         | Front 25x10x12, rear 25x10x12                                 | Front 25x10x12, rear 25x10x12                                 |
| Large ATV off-road tyres                         |         | Front 26x10x12, rear 26x10x12                                 | -   |
| <b>Passenger cabin</b>                           |         |   |   |
| Number of seats                                  |         | 1 driver's seat, 2 passenger seats (bench)                    | 1 driver's seat, 2 passenger seats (bench)                    |
| Roll bar   |         | Std.  | -   |
| Full cabin (heater included)                     |         | Opt.  | -   |
| Full cabin (heater and air conditioner included) |         | -   | Std.  |
| Opening windscreen (safety glass with wiper)     |         | Opt.  | Std.  |
| Doors (plastic, half-open)                       |         | Opt.  | -   |
| Doors (closed, with manual window opener)        |         | -   | Std.  |
| Sun canopy (plastic)                             |         | Opt.  | -   |
| Floor mat (rubber)                               |         | Opt.  | Std.  |
| Headrests  |         | Opt.  | Std.  |
| Speedometer                                      |         | Std.  | Std.  |
| Radio  |         | -   | Opt.  |
| Working lights (front)                           |         | Opt.  | Opt.  |

Specifications and details are subject to change without prior notification